EasyGates_____

ACCESS CONTROL QUALITY, RELIABLE, PIONEERING ACCESS SOLUTIONS FOR THE AUTOMATION INDUSTRY



ONLINE REAL TIME MANAGEMENT **KEYPADS** *PROXIMITY & RADIO READERS* **ELECTRIC & MAGNETIC LOCKS** – **AUDIO & VIDEO INTERCOMS TIMERS & RELAYS** 4G & GSM/GPRS CONTROLLERS

CONTENTS

ICON KEY	01
ONLINE REALTIME ACCESS CONTROL MANAGEMENT	02
INTERCOMS & KEYPADS	04
STANDALONE ACCESS CONTROL SYSTEMS	09
ACCESSORIES & ENCLOSURES	13
ELECTRIC AND MAGNETIC LOCKS	15
SWITCHES, BUTTONS & MISC ACCESSORIES	17

LOST A PRODUCT MANUAL?



PERSONALISED SERVICES



Personalise your products and raise your brand awareness with our state of the art laser etching service offered at highly competitive rates.

REMOTE CONTROLS, ENCLOSURES CE PLAQUES, PHOTOCELLS & KEYPADS

Access Control n. /'akses/ n. /kən'trəʊl/

Security features that control who can access resources or locations.

OPERATING

OPERATING METHOD



) GSM



MIFARE PROXY



MIFAR

RADIO FREQUENCY



MOBILE ACCESS





CUSTOMISABLE

FEATURES



ONLINE REALTIME ACCESS CONTROL MANAGEMENT

radio receiver kit 06-0129-EN

The HF Receiver Kit comprises of 2 parts housed in a single unit. Firstly, the 'Intrabox' GSM unit which stores data locally, but can be updated through its GPRS connection. Secondly, the HF Radio module which communicates and decodes the transmitters. Each device is uniquely coded and once programmed in via the online management suite, they cannot be programmed by another user.

This feature allows for sole management over a site / installation and guarantees all future sales of remotes to be directed through the installer.

- 868Mhz remote controls
- Dial to open feature
- Up to 10,000 users
- 3 month event log

- 2 NO relay outputs
- Email alerts
- 12-24V AC/DC
- 10 years FREE data

proximity reader kit 06-0131-EN

The Proximity reader kit is composed of 3 parts. Firstly, the 'Intrabox' GSM module which can be updated through its GPRS connection. Secondly, the Mifare reader, which can be mounted flush or surface with the addition of a back-box (optional extra). Thirdly, the relay card, which releases the door / gate it is operating and stores local proximity card codes.

Each device is uniquely coded, ensuring security over who can access and program proximity tags into the system.

With the ability to remotely add/change/delete proximity tags, this system gives your customer the freedom of choice for entry options.

- Mifare proxy tags
- Up to 1,000 users
- 3 month event log
- ▶ 1 NO / NC relay output
- Email alerts
- 12-24V AC/DC
- 10 years FREE data
- KEYPAD KIT 06-0130-EN

	\square			\frown	12/24
		()	(\mathbf{O})	((4)
			(v)		<u>\/12/12л</u>
\sim	\sim	\sim	\sim	\sim	<u> </u>

This new addition to the Intratone range also offers a variety of means for accessing an entrance. The keypad can store up to 80 separate codes, which can be split into time ranges across a 7 day period (including holiday's which can restrict use).

The GPRS module has an integrated RF module for the use of radio remote controls and also mobile entry as standard. This variety of access options offers the end user the freedom to choose how they want access to a door / gate.

All information stored is programmable via the online management suite, which offers security and data event logging.

- 868Mhz remote controls / mobile phone entry / coded entry
- Up to 10,000 users
- 2 NO relay outputs

- Email alerts
- 12-24V AC/DC
- Max. number of keypad codes 80
 - 10 years FREE data



INTRATONE

2 3

5 6

8 9



WHAT IS THE ONLINE MANAGEMENT SUITE, AND WHAT ARE ITS KEY FEATURES?

THE INTRATONE REAL-TIME MANAGEMENT SUITE allows the installer to take full control over their installations. This is provided by means of an online service which can program your intercoms, keyfobs, proxy tags, keypad codes and mobile entry numbers directly to the 4G/GSM unit supplied in every kit. On top of this impressive facility, the 4G/GSM device supplied comes complete with SIM and 10 years' worth of data/calls for access products (15 years for intercoms) at no extra cost.

The website is free to use, and comes packed with features to enable easy confiurgation, monitoring and updating of the full range of Intratone access control and intercom products.



MANAGE ALL OF YOUR SITES FROM ONE CENTRAL LOCATION! NO SITE VISITS, NO ONGOING COSTS, NO HASSLES!

FEATURES INCLUDE:

- Realtime changes
- Event log viewing
- Enabling/disabling
- Easy adding of users
- Time range management
- User group management
- Master controls for multi-sites
- Holiday ranges



DONT FORGET TO ORDER YOUR REMOTE CONTROLS/PROXIMITY TAGS (QUANTITY DISCOUNTS AVAILABLE)











INTERCOMS & KEYPADS

INTRACALL AUDIO INTERCOM (1 BUTTON)

The 'Intracall' intercom is a cost effective and easily managed GSM solution for door and gated entries. Not only is the system programmable via the online management suite, but also has integrated dial-to-open mobile phone entry. This is programmable for up to 1000 users.

The key benefit of this system is the 15 year call plan included FREE with the cost of the kit. This means no monthly costs for 15 years!

- Discreet profile (Only 88mm Wide)
- Calls 7 pre-programmed numbers per day
- Dial-to-open entry for up to 1000 users
- 1 x relay output
- Flush fitting (optional surface box available on request)
- 12-24V AC/DC



15 YEARS

UNLIMITED CALLS

& UPDATES

USERS WHO ARE GIVEN AN ACCESS NUMBER CAN CALL THE INTERCOM FOR AUTOMATIC ENTRY

UNLIMITED CALLS & U

& UPDATES

DDA AUDIO INTERCOM WITH KEYPAD & PROXIMITY READER

The DDA Audio intercom is a cost effective and easily managed GSM solution for door and gated entries. Not only is the system programmable via the online management suite, but also has integrated dial-to-open mobile phone entry.

The stainless-steel finish offers vandal resistance and weather resistance with a refined aesthetic look. Includes keypad and prox reader.

- High quality stainless steel finish
- Up to 40 keypad codes
- Proximity reader integrated
- Dial-to-open for up to 1000 users
- 1 x relay output (add up to 4)
- Priced per dwelling, please call for quote
- 12-24V AC/DC







USE THE **MANAGEMENT SUITE** TO SET UP TEMPORARY ACCESS CODES FOR NEW STAFF, CLIENTS, OR EVEN GUESTS. EASILY REMOVE AFTER USE FOR INCREASED SECURITY.

RENO VIDEO 4G INTERCOM WITH KEYPAD & PROXIMITY READER

The 'Reno' range is one of the more advanced series of intercoms we have to offer. It comes packed with features allowing for full colour video and audio calls to be made to any iOS or Android device. The data plan included in the price means no ongoing costs to the customer for 15 years! This includes all calls and updates made.

The callpoint consists of both coded keypad and proxy reader for end users with a digital scrolling display. Operational messages may also be programmed such as 'Call in progress'.

- Up to 40 keypad codes
- Mifare proxy / coded keypad / Mobile phone entry
- Up to 7,000 users (on prox & mobile Entry)
- 1 x relay output (add up to 4)
- Flush fitting (optional surface box available on request)
- 12-24V AC/DC
- Priced per dwelling, please call for a quote 15 YEARS! UNLIMITED UPDATES





MY INTERCOM APP KNOCK KNOCK!

The "My Intercom" app lets you see visitors directly on your smartphone or tablet, and gives you the ability to remotely allow or deny entrance to the caller.



PREDATOR WIFI WI-FI VIDEO INTERCO



The AES Predator Wi-Fi System offers high quality video communication to all mobile devices operating on iOS or Android technology. The Wi-Fi transmitter supplied with the kit can achieve a maximum range of 60m (dependant on the range of the router it is communicating with). Other technologies such as powerline adapters, or point-to-point Wi-Fi links can be used to increase this range and provide stable connections in areas prone to interference.

- 24V DC (adapter included)
- 1 relay output (NO & NC)
- Adjustable relay timings (1-10 Seconds)
- IP55



Keypad optional (3 x relay outputs)



PREDATOR WIFI PRO Predator VIEW ACTIVITY OUTSIDE YOUR GATES **RECEIVE VISITOR CALLS** Wiffi WITH VIDEO ON SMARTPHONE ALLOW / DENY ACCESS USING A SMARTPHONE UNLOCK **TAKE PICTURES & VIDEO** Download on the App Store GET IT ON OF VISITORS OR GATE AREA Google Play

(.,))

One of the newest key features is the free app available for download on Android and iOS. This app allows you access to all programmable features for the intercom, including keypad access codes, phone numbers for dial in / dial out, and the latest functions 'do not disturb' and 'out of hours'.

With all of these functions available on the app, this allows the programming of this intercom to be carried out within seconds and in a much more user friendly way.

- 15V DC (adapter included)
- 2 relay output (NO & NC)
- Dials out up to 4 numbers
- IP55



Dial to open functions up to 100 users

Modem models 2G quad band, 3G EU. 3G USA



CELLCOM PRIME APP





VIEW USER HISTORY

RIGHT FROM YOUR PHONE

DO NOT DISTURB! WATERSHED TIME



INBUILT SYSTEM CLOCK SET AUTO OPEN & CLOSE TIMES

AES DECT 603 WIRELESS AUDIO INTERCOM



The Dect 603 range is a radio based wireless intercom system that can operate with up to 4 handsets and has a maximum range of 250m. Being a 'dect' system significantly reduces the price when ordering multiple handsets for a single dwelling.

This range is also now available for multi-residence with kits available up to 4 way. Please contact us for further options available for this kit.

- 12-24V DC (adapter included)
- 2 Relay output (NO & NC)
- Adjustable relay timings (1-9 Secs)
- IP55 on speech module, IP65 for transmitter module Keypad optional (3 relay
 - outputs)
- 1.88GHz digital technology



The SC902AU is a sturdy wireless audio kit comprised of a MHF02X keypad and audio front panel combo, a wireless controller and SC100AU wireless audio handset, a vandal resistant faceplate to protect the front panel, and a SH804AX proximity key-fob for ease of access.

The kit is easy to use and is simple to set up and maintain. With the option to activate the door or gate release, and even turn on lighting via the designated buttons on the handset.

- Up to 250m range
- Electric lock / clean contact output
- Built in proxy reader
- Up to 4 call stations
- Up to 4 handsets per controller



DAITEM

000 00 000 0 30







The Farfisa 1PEXFD intercom is a one way audio kit, with Exhito indoor station (EX321) and Profilo external station (PL11PED), equipped with access and control keypad (FC52PL). This model also includes a surface mount back box.

- 2 Wire audio system
- Integrated backlit keypad (2 x relays)
- Up to 200m
- Rain shelter included
- Clean contact output / 12V output



The Videx 4000 Series audio entry kit with 3 code, 3 relay coded access keypad and 1 call button and back lit name plate. Features include electronic call tone and timed door release (1-99 seconds or latching).

The kit comprises an entry panel, a telephone and AC PSU. The telephone includes a three position volume control and is wall mountable. Up to 2 additional handsets can be connected in the same apartment. The programming of access codes is carried out using the codelocks keypad, codes can be 4-8 digits.

- 3 Wire audio system
- Backlit keypad (3 x relays)
- Surface mount
- Built-in lock relay



Our "EASY" range of keypads cover all needs, from standalone to online, including advanced features such as selectable backlighting, heating, anti-tamper and bypass mode. This keypad has proven its deserved status as our best seller.

Available with either pre-formed 1.5M cable or terminal connections, all three having fully potted/sealed electronics providing maximum all weather protection.

Power supply: 12-24 Vac/dc Power consumption: up to 500 mA Memory capacity: 500 codes Nr. relay output: 2 Relay capacity: 2 A Auxiliary input: N.C. / N.O. Indicators: 2 two-color (red/green) LEDs + buzzer Operating T°: -20°C / +55°C Protection rating: EASYBKR=IP65 / EASYBKA=IP65 Size and weight: 120 x 76 x 21mm - 410g

ALSO AVAILABLE EASYBKW FOR ACCESS CONTROL SYSTEMS

Power supply: 12-24 Vac/dc **Power consumption:** 50 mA **Protocol:** 26/30 bit Wiegand - data clock **Operating T°:** -20°C / +55°C **Protection rating:** IP67 **Size and weight:** 120 x 76 x 27mm – 410g

MAJOR BRANDS OF KEYPADS AVAILABLE ON OUR TRADE STORE! LOGIN TO WWW.EASYGATESDIRECT.CO.UK TO SEARCH OR CALL US







٥	6	
12	3	
4 5		
78		
	and a	

CDVI LiftMaster





SFARFISA

STANDALONE ACCESS CONTROL SYSTEMS

At EasyGates Direct we pride ourselves on our access control knowledge, providing anything from a simple replacement remote control all the way through to advanced GSM based access control systems for thousands of users. Our expert presales technical team are available over the telephone or can visit a site with you to provide advice and customised solutions.

PRASTEL RADIO REMOTE CONTROL SYSTEMS

PRASTE

Our Prastel radio range enables the installer to provide secure coded systems that are scalable and cost effective. Each receiver can be coded with a unique installer ID and each remote laser etched with the installer logo and contact details, ensuring repeat business is maintained.







ENSURE REPEAT BUSINESS! LOCKS RECEIVER TO THE INSTALLER!

GT+ is a handheld programming tool for all Prastel radio products. It enables installers to modify their sites through directly connecting to receivers or precoding remote controls with relevant data for easy enrolling or disabling.



USB or powers from MR Receiver
 Manages all Prastel receiver types

Dimensions: 140x 65 x30mm

- Codes Prastel 433Mhz remotes
- Stores site data locally
 BC software class supplied
- PC software also supplied



PROX/RADIO COMBINED SYSTEMS

M2000-BT

The M2000-BT is an access control unit. It includes a 2000-user memory, 2 external reader inputs and a 433 MHz radio receiver.

The key innovation lies in the simple and wireless unit management and programming (via Smartphone).

- 2000 users
- Built-in 433 MHz radio receiver
- 2 Wiegand reader inputs 26, 30, 37 bits or data clock
- 4 auxiliary inputs (2 push-buttons, 2 magnetic loops)
- Anti-passback (hard)
- Event recording (3000 entries, FIFO)
- 8 User time slots, 32 groups, Holidays & special days
- Programming: via smartphone (compatible with Android®and iPhone®) management of user full names, programmable time slots and event visualisation
- ABS box with double hook : screw or DIN rail mount



MR-GSM ONLINE RADIO CONTROLLER

The MR-GSM Prastel access control unit can manage the site memory content remotely and in real time via GPRS network.

With the WinAccess software connected to the Internet, the site administrator can carry out many operations on the connected modules: addition, replacement, removal, history of transmitter numbers, badge numbers and accepted or denied codes.

- Built-in 433.920 MHz radio receiver, 2 channels
- 1000 code memory
- Modem GSM/GPRS 4 bands
- Wiegand or 2 alarm inputs Connect up to 6 MR series receivers on RS485 bus

PRASTEĽ



MPROXMINI is a 125 kHz proximity reader, compatible with all access control units that accept Wiegand 26/30 bit or data clock protocols.

All the electronic components and the internal antenna are assembled in a completely resinated case that offers a high degree of weather resistence (IP67).

- 12Vdc power supply
- 20 mA power consumption
- -20°C / +55°C operating temperature
 IP67 protection rating





PROX CARDS & TOKENS FOR PRASTEL CONTROLLERS

HAVE A LARGE



MTAG

Proximity tag 125 kHz

MBPRO Proximity badge 125 kHz

(**7**)

INTRATONE RADIO SYSTEM INTRATONE RECEIVER MODULE + USB PROGRAMMING UNIT

The Intratone 07-0106 RF receiver module facilitates not only a cost effective means for radio access control, but also offers security with its 'read / write' technology. This enables the owner / installer to program remote fobs from the office and ship directly to site without any callouts and tedious local programming into the receiver. All of this can be managed online, so if a remote is lost, a replacement can be programmed and dispatched in its place rendering the missing one obsolete and no longer functional. The easy to use USB programmer enables swift execution of configuring remotes, so large jobs with multiple remote fobs can be catered for in no time at all.

The receiver itself boasts an impressive 2500 users, programmable relay timings, 2 NO relay outputs, external antenna input, and an IP67 enclosure. The key feature of this receiver is that all future sales of remote fobs must be directed through the account holder for the online management area. This offers guaranteed repeat sales, and more importantly additional security on every installation.

- Voltage: 12/24V AC DC
- Frequency: 868Mhz
- Rating: IP67

- RF type: rolling code
- Size: 90mm x 129mm x 37mm
- Output: 2 x NO Relays







ENQUIRE TO UPGRADE YOUR GATE AUTOMATION KIT

ELDES ESIM320 gsm switch controller

The ELDES gate controller is a remote GSM and GPRS device, that allows remote triggering of configured outputs. The Relays can be activated by an authorized phone call, text message or mobile application (iOS and Android).

Up to five administrators can configure the device via the internet or SMS, where they can add/maintain up to 2000 users. 8 timed/scheduled access periods can be customised to authorise or refuse activation requests.

The ELDES gate controller can be used for a multitude of applications, but was specifically designed to operate barriers and garage doors.

- Dial to open gates (no phone costs)
- Use caller ID to identify user
- SMS notification of fault/failure
- Domestic & commercial application
- Various enclosure options
- Event log
- No response if number not recognised
- Schedule timed automatic operation
 - 2 Relays, 3 Inputs
- Demonstration videos on YouTube



PROGRAM VIA SMS



Download on the App Store

OR BY USB & PC SOFTWARE



ESIM320 CAN BE ACTIVATED VIA CALL, APP, OR SMS

MONITORS AND SENDS





Get IT ON Google Play

ACCESSORIES **POWER SUPPLIES FOR ACCESS CONTROL**



- Can be installed on DIN rail TS-35/7.5 or 15
- **Isolation class 2**
- LED indicator for power on



- **Universal AC input/Full range**
- **Protections: Short circuit/Over**
 - load/Over voltage
- Cooling by free air convection



- 100% full load burn-in test
- **3** years warranty

MODEL	DR15-12	DR15-24	DR30-12	DR30-24	DR60-12	DR60-24
VOLTAGE	12V	24V	12V	24V	12V	24V
RATED CURRENT	1.25A	0.63A	2.0A	1.5A	4.5A	2.5Aa
RATED POWER	15W	15.2W	24W	36W	54W	60W
ADJ. RANGE	10.8 - 13.2V	21.6 - 26.4V	10.8- 13.2V	21.6 - 26.4V	11.1 - 13.2V	21.6 - 26.4V
WORKING TEMP.	-20 +60°C	-20 +60°C	-20 +60°C	-20 +60°C	-20 +60°C	-20 +60°C
SIZE (WxHxD)	25x93x56mm	25x93x56mm	78x93x56mm	78x93x56mm	78x93x56mm	78x93x56mm

SINGLE POLE RELAYS 12 OR 24V

- **DIN** rail relay module
- Switches up to 250V 6Amp from 12/24V input
- NO & NC output

Highly useful indicator LED Two variations:





- Easy to program TH827 (select voltage when orderina)
- Digital display robust LCD screen
- Weekly and daily programming day and hour indication
- CMOS quartz technology, micro-processor
- **Program repeat**
- Memory backup battery
 - 3 operating modes (automatic, on, off)
 - Reset button 7-day timer



SPECIAL MULTI-FUNCTION TIMER RELAY 12 - 230V 12/230



FLASHING LIGHT PULSE FUNCTION



MAGLOCK DELAY FUNCTION



FOR CABLES, CONDUITS & TOOLS PLEASE CHECK OUT OUR TRADE STORE! LOGIN TO WWW.EASYGATESDIRECT.CO.UK TO SEARCH OR CALL US



0845 054 5070

EasyGates Direct

ENCLOSURES FIBOX ARCA CABINETS

The FIBOX ARCA cabinets are a range of high quality enclosures for the packaging and protection of electrical and electronic components and systems. Enclosures come with standard shelf configuration.

The high performance UV stabilised polycarbonate cabinets are lightweight, long lasting, chemical resistant, and non corrosive for use in harsh and demanding environments. The cabinets are also water and high impact resistant for protection against vandals and the elements.

DOOR

- Door opening angle 120°
- Both landscape and portrait option
- Pre-formed fixing studs inside
- Easy access to contents

► LOCKING

ARCA 705030

ARCA 806030

- Double-bit
- Changeable lock inserts
- **MOUNTING PODS**
- On the base, cover and four base sides

TVV

► GASKET

- Wide and secured gasket with PUR material for high quality sealing
- Special molded rib design makes the cabinet stable and solid
- Double corner to secure fixing without destroying the IP rating
- Declined base design for better waterproofing
- Patent pending hinge design for easy assembly and refined appearance
- Robust and rigid cabinet

CUSTOMISE YOUR PRODUCTS WITH OUR LASER ETCHING SERVICES. PROFESSIONAL LOOK, PRE-BUILT CABINETS FOR AUTOMATION, ACCESS AND MACHINERY APPLICATIONS!



700x500x300mm

800x600x300mm



ELECTRIC AND MAGNETIC LOCKS

ELETTRIKA ELECTRIC GATE LOCKS

The CISA Elettrika has a pull resistance of up to 2000kg, excellent vibration resistance and impact strength thanks to its protective steel case, which completely encloses around the lock and striker. The Elettrika is 'non-handed' and with an available backset from 50mm to 80mm.

- Electric hold open function
- Backset can be regulated from 50mm to 80mm
- 12V AC
- Holding force of 2000KG
- Strong steel exterior casing
- Rotary hook deadbolt
- Fail secure



The PLA10/11 electric locks were specially designed for installation on manual or automatic outside outward opening doors and drive-through gates. This type of opening is necessary when the door/gate is situated on a slope or when safety regulations foresee an outward-opening escape route in the event of an emergency. The characteristics and finish make it ideal for installation even in surroundings subject to considerable temperature ranges.

- 12V AC 15VA
- ▶ 1.3Kg

- 65mm x 33mm x 120mm
- Galvanized steel case & cover

CISA

1A721

1A731

Nice

ELKA LOCKS OPTIMUM SAFETY DEVICES

The **M315** is an ELKA motor lock that has a stroke of 150mm with a stainless steel pin 30^ømm, complete with an emergency release by standard type cylinder lock. Includes M090 controller.

- Reporting back OPEN/CLOSED to access possible, complete with controller MO90
- For universal use with all gate controllers with warning light connection
- Pre-warning time (potential-free or 24V or 230V)
- 24Vdc
- (LxWxH) 146mm x 146mm x 440 mm
- 13.0kg
- Max. 150mm stroke
- Stainless steel pin 30^ømm



The **E205** is an ELKA electromagnetic bolt lock system. Complete with stainless steel pin 20^ømm, 50mm stroke, for all ELKA-24V swing gate openers and can lock either down, sideways or up.

- For all ELKA-24V swing gate openers
- Locks up, down and sideways
- Stainless steel pin
- 50mm stroke
- Emergency release with key (cylinder lock)
- 24Vdc (alternating current)
- (LxWxH) 58mm x 92mm x 298 mm
- IP43 rating







MAGNETIC DOOR LOCKS

ES400/500



Features: ES400 - 400KG ES500 - 500KG

- Stainless steel construction. (IP54)
- Fail safe & monitored
- Electronics internally protected
- Flush and surface versions

Face & side mount (surface magnets)

Technical Specifications:

- Voltage:
 - Current:





Features:

- Max holding force
 363kg/ 544kg
- Stainless/brushed stainless steel
- Monitoring sensor
- Standard fixing

Technical Specifications:

- Voltage: 12Vdc/24Vdc
- Current: 12Vdc: 500 mA
 - 24Vdc: 250 mA

Z&L BRACKETS



Our range of Z & L Brackets provide multiple mounting solutions for 180/300/400 & 500kg Magnetic locks.

- Satin anodised aluminium
- Powder coated steel (external magnets)
- Adjustable/ architectural and external brackets

CABLE CONDUITS & FITTINGS

20MM PVC CORRUGATED FLEXIBLE CONDUIT 20101101 **20MM PVC 100 METERS BLACK - 20MM CONDUIT SPACER CONDUIT COUPLER CONDUIT ADAPTER** Male & Female **20MM PVC** SPECTION PARTS ONDUIT BOXES **10M BLACK - 20MM FLEXIBLE CONDUIT** + 10 GLANDS CONTRACTOR PACK Inspection T Angle Boxes, Through Boxes, Terminal Boxes Inspection Elbow & many more

SWITCHES, BUTTONS & MISC ACCESSORIES

FIREMAN SWITCHES

Fireman switches are access switches for the use of emergency services. In the event of an incident they can be used to cut the power to the building if it is necessary.

COM / NO / NC change-over-contacts



CDVI DIGIWAY KEYSWITCH

- **Stainless steel**
- Supplied with 2 keys
- 3-position keyswitch: Auto, Door Free, Door Open
- Dimensions: 85 x 85 x 2 (mm)
- Flush & surface available





Brushed stainless steel

Flush & surface available

Standard Stainless Exit Button Standard Surface: 85 x 85 x 30mm Standard Flush: 85 x 85 x 2mm

- Flush or surface
- **Stainless steel**
- High impact buttons
- UK back-box format
- External or internal use



DRB-004F

Domed Stainless Exit Button Standard Surface: 85 x 85 x 30mm Standard Flush: 85 x 85 x 2mm

- Flush or surface
- **Stainless steel**
- High impact buttons
- UK back-box format
- External or internal use



CDVI EM201

Double-pole, resettable emergency door release. 86 x 86 x 50mm.

- **Emergency unlock**
- Resettable
- Double-pole as standard
- UK back-box format
- Internal use
- Reset keys included

DDA COMPLIANT BUTTO

Our DDA compliant range of access buttons are robust and reliable, designed with easy visibility to spot with large engraved text, these buttons are ideal for hospitals and care homes.

PUSH TO OPEN PUSH TO

- Push to make & break
- Flush & surface available
- **High quality stainless steel Suitable for DDA environments**



VISIT EASYGATESDIRECT.CO.UK FOR

A HUGE RANGE OF SWITCHES, BUTTONS AND ELECTRICAL ACCESSORIES. CUSTOMISE YOUR PRODUCTS WITH OUR LASER ETCHING SERVICES!



WE ALSO STOCK A VAST **RANGE OF TOOLS AND TOOL KITS FOR ALL YOUR INSTALLATION & MAINTENANCE NEEDS**





GATE & GARAGE AUTOMATION ACCESS CONTROL GATE SAFETY INTERCOMS & KEYPADS **SPECIALISED PHOTOCELLS OEM DESIGNED PRODUCTS CUSTOMISED RADIO SYSTEMS**



1000'S OF PRODUCTS at great prices!





Dedicated team offering pre / post-sales support and technical advice via phone, email, forum or live chat.

MANUALS & GUIDES

Easy to view and download completely free. No sign up needed! Start today. manuals.easygates.co.uk

8	
2	
3	
2	
3	
5	

TRAINING
FACILITIES
Gate safety legislation force testing

safety edge assembly and more.



PERSONALISED PRODUCTS Personalise your installations with our laser etching service.

To find out how EasyGates Direct can supply tailor-made solutions to your business, contact:

WWW.EASYGATESDIRECT.CO.UK



01384 569 942



INFO@EASYGATESDIRECT.CO.UK



EASYGATESDIRECT



Raising Standards Safety Assured



@EASYGATES

UNIT 16 JAMES SCOTT ROAD, HALESOWEN, WEST MIDLANDS, B63 2QT